

25t吊移動式クレーン 定格総荷重早見表

機種：TADANO：GR-250N-5 ブーム作業・主巻フック(220kg)使用時

ブーム定格総荷重表(メーカー主要所元より)

吊荷+吊具の重量 (定格総荷重 × 0.9 -0.22)

下記の数値はクレーンの100%の性能であり赤ランプが点灯するので、この数値だけで作業半径を定めるのはNG!

下記の数値が緑ランプ点灯の状態ですることができる重量『吊荷+吊具』の重量が、下記の重量未満で定めればOK!

アウトリガ最大張出 (6.6m) 全周

ブーム長さ	9.35m	16.40m	23.45m	30.50m	
作業半径	2.50m	25.00t	18.00t	12.50t	
	3.00m	25.00t	18.00t	12.50t	
	3.50m	25.00t	18.00t	12.50t	8.00t
	4.00m	23.50t	18.00t	12.50t	8.00t
	4.50m	21.50t	18.00t	12.50t	8.00t
	5.00m	19.60t	18.00t	12.50t	8.00t
	5.50m	17.80t	17.00t	12.50t	8.00t
	6.00m	16.30t	16.00t	12.50t	8.00t
	6.50m	15.10t	15.00t	12.50t	8.00t
	7.00m		14.00t	11.50t	8.00t
	8.00m		11.40t	10.20t	8.00t
	9.00m		9.00t	9.00t	8.00t
	10.00m		7.80t	7.60t	7.15t
	11.00m		6.50t	6.65t	6.40t
	12.00m		5.55t	5.80t	5.60t
	13.00m		4.75t	5.00t	4.90t
	13.50m		4.45t	4.65t	4.60t
	14.00m			4.35t	4.40t
	15.00m			3.85t	3.90t
	16.00m			3.40t	3.45t
17.00m			3.00t	3.05t	
18.00m			2.65t	2.70t	
19.00m			2.10t	2.40t	
20.00m			2.00t	2.15t	
20.50m				2.05t	
21.00m				1.95t	
22.00m				1.75t	
24.00m				1.40t	
26.00m				1.10t	
27.90m				0.90t	

左の緑ランプ点灯の状態では右の数値を使用!

アウトリガ最大張出 (6.6m) 全周

ブーム長さ	9.35m	16.40m	23.45m	30.50m	
作業半径	2.50m	22.28t	15.98t	11.03t	
	3.00m	22.28t	15.98t	11.03t	
	3.50m	22.28t	15.98t	11.03t	6.98t
	4.00m	20.93t	15.98t	11.03t	6.98t
	4.50m	19.13t	15.98t	11.03t	6.98t
	5.00m	17.42t	15.98t	11.03t	6.98t
	5.50m	15.80t	15.08t	11.03t	6.98t
	6.00m	14.45t	14.18t	11.03t	6.98t
	6.50m	13.37t	13.28t	11.03t	6.98t
	7.00m		12.38t	10.13t	6.98t
	8.00m		10.04t	8.96t	6.98t
	9.00m		7.88t	7.88t	6.98t
	10.00m		6.80t	6.62t	6.22t
	11.00m		5.63t	5.77t	5.54t
	12.00m		4.78t	5.00t	4.82t
	13.00m		4.06t	4.28t	4.19t
	13.50m		3.79t	3.97t	3.92t
	14.00m			3.70t	3.74t
	15.00m			3.25t	3.29t
	16.00m			2.84t	2.89t
17.00m			2.48t	2.53t	
18.00m			2.17t	2.21t	
19.00m			1.67t	1.94t	
20.00m			1.58t	1.72t	
20.50m				1.63t	
21.00m				1.54t	
22.00m				1.36t	
24.00m				1.04t	
26.00m				0.77t	
27.90m				0.59t	